RENO® LIGHTING

PRIME



Luxor

Backlit Flat Panel



Product Description

The Luxor Metric Backlit Flat Panel features a slim, contemporary design with even light distribution. Its advanced technology supports multiple light configurations, making it adaptable for a variety of applications. Proven efficient, this panel delivers uniform illumination with a long, maintenance-free lifespan.

Specifications

120-347V
30W, 40W, 50W, 60W (selectable)
3500K, 4000K, 5000K (selectable)
Up to 149 lm/W
Up to 8,725 lm
CRI 80+

L70@ 100,000 hours
Beam Angle 125°
0-10V Dimming
Operating Temp: -4°F to +122°F | -20°C to +50°C
T-Grid and Suspension Mounting

Easy-Lay in Installation

Fits 500mm x 1,500mm metric ceiling systems.

Dimensions

Width: 501mm (19.7″)
Height: 34mm (1.3″)
Length: 1517mm (59.7″)

Backlit Technology

For even light distribution without shadowing.

Damp Rated

Suitable for Damp Locations.

PMMA Lens

Prevents yellowing.

30W, 40W, 50W, 60W

Selectable Watts

4,417 - 8,725 lm

Delivered Lumens

Applications

Commercial
Warehouse
Multi-residential
Retail

Order Guide

Order#	Model	Wattage	Voltage	Lumens	Efficacy	CCT
R35308	RENO-2060BLPL-UNV/347-MWMCCT	30/40/50/60W	120-347V	Up to 8,725 lm	Up to 149 lm/W	35/40/5000K

Mounting Accessories



R39204

Order#	Model	Description
R39204	RENO-RP-ROPE	Aircraft Suspension Cable for 20x60 fixture

Emergency LED Drivers



R83001

Order#	Model	Description
R83001	RENO-EM-H15	Emergency LED Driver (100-347V AC, 50-60Hz, 15W)



PRIME

US Office
8735 Dunwoody Place #6728
Atlanta, GA
30350 United States

RENO® LIGHTING

CA Office
9133 Leslie St. #120
Richmond Hill, ON
L4B 4N1 Canada

info@renolighting.com | www.renolighting.com