

INSTALLATION INSTRUCTIONS

Constant Voltage Dimmable LED Driver

BEFORE YOU START:

- Read and follow all instructions
- Reference local electrical codes
- Mount power supply at a height greater than 1 foot.

NOTE: 100% to 20% Dimmable.

To ensure good dimming results, the driver requires a minimum load of 10%-100% of total capacity. Working temp is -13F to 104F. Drivers are dimmable with the following dimmers.

Recommened Dimmers LUTRON DVLV600 LUTRON DVCL153

SAFETY WARNING: Reference the National Electrical Code regulations. Installation work and electrical wiring should be doneby qualified person(s) in accordance with all applicable codesand standards. Modifying or disassembling beyond instructionswill void the warranty for this product. Do not submerge or install within 5 feet of a swimming pool. Failure to follow safety warnings, and installation instructions will void the warranty for this product.

DRY/ DAMP LOCATION ONLY






FIG.1




	Model No.	Size	Voltage / Watts	Weights	
L	RENO-HBL096-DC24V	6.97"L x 2.76"W x 1.40"H	24V / 96W	1.5 lbs.	

To calculate total watts multiply (Watts per ft.) x (Total Length of Run) = Total Watts It is recommended to have 10% - 100% loading for optimal performance.

FIG.2





料号: RUG00065 RENO 20W-96W电源通用 说明书A4纸 单面印刷 需折页