RODUCT HIGHLIGHTS



Key Features

- Slim, canless, rotatable gimbal design
- 2-hour fire rated (UL263, ASTM E119, CAN ULC S101)
- Five selectable CCTs (27/30/35/40/5000K)
- Type IC rated for direct insulation contact

Quick Specs

Si	ze	Watts	Voltage	Lumens	ССТ
4	11	9W	120V	900 lm	27/35/40/5000K



Key Features

- A unique architectural look to modernize any property
- Multi Power, Multi CCT & Dual Voltage (120-347V)
- IP65 Rated for outdoor locations
- Built-in photocell included
- R1 (24/32/40W) model also available. Scan for info!

Quick Specs

Watts	Lumens	ССТ	Finish
48/64/80W	6,480/8,640/10,800 lm	30/40/5000K	Black



Key Features

- Multi Power, Multi CCT & Dual Voltage (120-347V)
- Integrated sensor for even greater energy savings
- Suitable for damp locations
- Includes coverplate (surface mount) and V-hooks (suspension)
- 2FT length/models without sensor available. Scan for info!

Quick Specs

Size	Watts	Lumens	ССТ	
4FT	30/40/50W	3,900/5,200/6,500 lm	35/40/5000K	



Key Features

- 30% slimmer design with a sleek architectural flair
- Multi Power, Multi CCT & Dual Voltage (120-347V)
- IP65 Rated for outdoor locations
- IDA DarkSky approved
- R1 (25/40/60W) model also available. Scan for info!

Quick Specs

Watts	Lumens	ССТ	Finish
75/100/120W	9,375/12,500/15,000 lm	30/40/5000K	Black

CONTACT YOUR REP FOR PRICING!

More info? renolighting.com

Questions? 905-604-4666





At RENO, we're commited to being Always On.™

Always On Innovation

Our very own R&D facility enables us to conceptualize and develop innovative lighting solutions that fit every project's needs.

Always On Service

Our dedication to speed, attention to detail, and indepth lighting knowledge is why customers love us.

Always On Your Side

Our relationship does not end after the sale. We promise to always be on your side, long after you've installed our products.